

Part Numbers:

Part Number	Description	Application
240S3E-9.0	This controller is suitable for 240VAC 3-Wire motors up to 1.5kW (2.0HP)	Light Commercial Doors, Heavy Duty Cycle Roller Shutters, Sectional Doors, Garage and Sliding doors
240S3E-12	This controller is suitable for 240VAC 3-Wire motors up to 2kW (2.6HP)	
240S4E-9.0	This controller is suitable for 240VAC 4-Wire motors up to 1.5kW (2.0HP)	Light Commercial Doors, Heavy Duty Cycle Roller Shutters, Sectional Doors, Garage and Sliding doors
240S4E-12	This controller is suitable for 240VAC 4-Wire motors up to 2kW (2.6HP)	

Key switch



AUTO: When the key is in the AUTO position the controller (motor) can be operated by :

- Wireless remote control if the receiver is installed
- Push button input on the circuit board which can be used to connect external push buttons, swipe card, loop detectors or keypads
- Pedestrian access input on the circuit board which can be used to connect external push buttons, swipe card, loop detectors or keypads
- Stop button on the front of the case

In AUTO mode the Open and Close button on the front of the case are disabled.

OFF: When the key is in the OFF position, the controller (motor) does not work. The push buttons and the wireless remotes are disabled.

MANUAL: When the key is in the MANUAL position the controller (motor) will only operate with the push buttons that are on the front panel. Wireless remote controls are disabled.