



## Part Numbers:

Part Number	Description	Application
<b>MCi415-2.4</b>	<p>Suitable for 3-phase motors up to 1 kW (1.3HP). Thermal overload adjustable from 1.6-2.4Amps.</p> <ul style="list-style-type: none"> <li>• UP / DOWN / STOP external push buttons</li> <li>• External key switch</li> </ul>	Commercial Doors, Heavy Duty Roller Shutters, Sectional Doors, Garage and Sliding doors
<b>MCi415-4.0</b>	<p>Suitable for 3-phase motors up to 1.6kW (2.2HP). Thermal overload adjustable from 2.4-4.0Amps.</p> <ul style="list-style-type: none"> <li>• UP / DOWN / STOP external push buttons</li> <li>• External key switch</li> </ul>	Commercial Doors, Heavy Duty Roller Shutters, Sectional Doors, Garage and Sliding doors

## Key switch



**AUTO:** When the key is in the AUTO position the controller (motor) can be operated by:

- Wireless remote control
- Push button input on the circuit board which can be used to connect external push buttons, swipe card, loop detectors or keypads
- Stop button on the front of the case

In AUTO mode the Open and Close button on the front of the case are disabled.

**OFF:** When the key is in the OFF position, the controller (motor) does not work. The push buttons and the wireless remotes are disabled.

**MANUAL:** When the key is in the MANUAL position the controller (motor) will operate with the push buttons that are on the front panel and other inputs on the control card. Wireless remote controls are disabled.